

+2°C~+8°C

## Medical Refrigerator



# Constance

*Ultimate German Refrigeration  
Technology*

## LT02-260U



### Control System:

- Microprocessor controller, temperature ranging from +2°C to +8°C, can be set freely, controlling precision 1°C, display accuracy 0.1°C. Room temperature ranging from 0°C to 32°C.
- Combined with two exact sensors and auto defrost
- Audible and visual alarm: High or Low Temperature Alarm, Door Open Alarm, Sensor Failure Alarm.
- Power Supply: 220V / 50Hz, 1 phase.



### Structure Design:

- Upright type, exterior made from powder coated steel, interior made from ABS.
- Lockable double-layer electrical heating glass door can prevent condensation on the door.
- Interior Fluorescent lighting
- Optional: Chart recorder, printer.



### Refrigeration System:

- Germany EBM fan motor.
- Force air circulation system.
- R134a, CFC free refrigerant.
- Highly effective condenser and expansile evaporator to provide quick freezing.
- Certification: ISO9001, ISO14001, ISO13485.



### Specification:

Model	Capacity	External Size (WxDxH)mm	Internal Size (WxDxH)mm	Input Power (W)	Number of Shelves	Weight (N.t/Gt) Kg
LT02-260U	260L	575 x 583 x 1690	490 x 485 x 1172	150	3+1	68 / 73