

LT02-275C

Constant Temperature under Intelligent Control

High-precision computerized temperature control system: The cabinet has built-in high-sensitivity temperature sensors, ensuring a constant temperature inside it.

Security System

The well-developed audible & visual alarm system (with multiple audible & visual alarm functions, such as high temperature alarm, low-temperature alarm, sensor failure alarm, door opening alarm, power outage alarm) makes it safer for storage.

High-efficiency Refrigeration

Equipped with environmentally-friendly Freon-free refrigerant R134a and compressor supplied by an international famous brand, the refrigerator is characterized by fast refrigeration and low noise.

Human-oriented Design

Power on/off key (the button is located on the display panel);

Power-on delay time setting function;

Start-delay time setting function (solving the problem of simultaneous startup of batch products after power failure);




Scope of Application

Suitable for storage of biological products, vaccines, drugs, reagents, etc. Suitable for use in pharmacies, pharmaceutical factories, hospitals, centers for disease prevention & control, clinics, etc.

Performance Data / Cooling Curve



External Dimensions



Specification Chart

Model LT02-275C Cabinet Type Chest Capacity(L) 275 Internal Size(W*D*H)mm 1019*465*651 External Size(W*D*H)mm 1245*775*929 Package Size(W*D*H)mm 1332*810*975 NW/GW(Kgs) 87/94 Performance Temperature Range Ambient Temperature 10-43°C Cooling Performance 4°C	
Capacity(L) 275 Internal Size(W*D*H)mm 1019*465*651 External Size(W*D*H)mm 1245*775*929 Package Size(W*D*H)mm 1332*810*975 NW/GW(Kgs) 87/94 Performance Temperature Range 2~8°C Ambient Temperature 10-43°C Cooling Performance 4°C	
Internal Size(W*D*H)mm 1019*465*651 External Size(W*D*H)mm 1245*775*929 Package Size(W*D*H)mm 1332*810*975 NW/GW(Kgs) 87/94 Performance Temperature Range 2~8°C Ambient Temperature 10-43°C Cooling Performance 4°C	
External Size(W*D*H)mm 1245*775*929 Package Size(W*D*H)mm 1332*810*975 NW/GW(Kgs) 87/94 Performance Temperature Range 2~8°C Ambient Temperature 10-43°C Cooling Performance 4°C	
Package Size(W*D*H)mm 1332*810*975 NW/GW(Kgs) 87/94 Performance Temperature Range 2~8°C Ambient Temperature 10-43°C Cooling Performance 4°C	
NW/GW(Kgs) 87/94 Performance Temperature Range 2~8°C Ambient Temperature 10-43°C Cooling Performance 4°C	
Performance Temperature Range 2~8°C Ambient Temperature 10-43°C Cooling Performance 4°C	
Temperature Range2~8°CAmbient Temperature10-43°CCooling Performance4°C	
Ambient Temperature 10-43°C Cooling Performance 4°C	
Cooling Performance 4°C	
Climate Class N	
Controller Microprocessor	
Display Digital display	
Refrigeration	
Compressor 1pc	
Cooling method Direct cooling	
Defrost Mode Automatic	
Refrigerant R290	
Insulation Thickness(mm) 110	
Construction	
External Material SPCC epoxy coat	ing
Inner Material Stainless steel	
Coated Hanging Basket 1	
Door Lock with Key Yes	
Backup battery Yes	
Casters 4 (2 caster with	brake)
Alarm	
Temperature High/Low tempe	rature,
Electrical Power failure , Lo	ow battery, Relay
System Sennor error	
Electrical	
Power Supply(V/HZ) 220/50	
Rated Power(W) 190	
Input Power(W) 275	
Power Consumption(KWh/24h) 0.45	
Rated Current(A) 1.25	
Options Accessory	
System USB	

 $^{{}^\}star\! \text{The model}, parameters and performance specified in this brochure may be changed without prior notice because of product upgrading.}$



^{*}There may be differences between the product images shown in this brochure and the actual products. When you are buying any product, please check the actual product.