



Technology



LT02-520





Control System:

- Microprocessor controller, temperature ranging from +2°C to +8°C, can be set freely, controlling precision 1°C, display accuracy 0.1°C. Room temperature ranging from 0°C to 32°C.

- Combined with two exact sensors and auto ddefrost.

- Audible and visual alarm: High or Low Temperature Alarm, Door Open Alarm, Sensor Failure Alarm.

- Power Suuply: 220V / 50Hz, 1 phase.



- Upright type, exterior and interial material are of stainless steel.
- 4pcs of caster.
- Loackable two-layer glass door.
- With build-in fluorescent lighting.
- 4 adjustable steel wire shelves.
- Temperature printer with recording up to 7 days.
- backup battery up to 72 operating hours.
- Optional: Chart recorder.



Refrigeration System:

- Germany EBM fan motor.
- Force air circulation system.
- R134a, CFC free refrigerant.
- Highly effective condenser and expansile evaporator to provide quick freezing.
- Certification: ISO9001, ISO14001, ISO13485.



Specification:

Model	Capacity	External Size (WxDxH)mm	Internal Size (WxDxH)mm	Input Power (W)	Weight (N.t/Gt) Kg
LT02-520	520L	710 x 730 x 2000	590 x 670 x 1450	350	150 / 160

